### **Production Description:**

# $Introduction \square$

Boreway diamond cup grinding wheels are usually used with large grinding machine and othe r hand-

held grinding machines, these diamond cup grinding wheels are designed for the restoration or maintenance of granite, marble, and many other stone surface,

Boreway diamond cup grinding wheels are polishing with quick speed and without scratch.

Our professional **diamond cup grinding wheels** are designed to ensure fast grinding and finishing of concrete, granite, and other stones in dry or wet conditions. Our diamond grinding wheels are available in three grits: coarse (30/40 grits) for fast stock removal, medium (70/80 grits) for moderate grinding, and fine (100-120 grits). We offer both diamond cup wheels with 5/8-11 thread, and velcro backed diamond grinding wheels for grinding concrete counter tops.

**Using sequence** From the thick number to the number, Polishes finally.

**Advantage** Our products export to Brazil, India, Australia, USA, Ukraine, Italy, Poland, Russia, more than 20 different countries. In these overseas markets, our cup grinding wheels enjoy a good reputation, we get good feedbacks about their corresponding test result, and al so a long lifespan. so, we are confident in our products quality.

All of our our products have been strictly tested before access to market.

Other specification can be ordered by client.

#### **Detailed Images:**

#### **Turbo Segment Diamond Cup Grinding Wheels:**

Turbo segment diamond cup grinding wheels are designed for surface restoration or mainten ance of granite,marble,concrete and other stone.

These diamond cup grinding wheels are suitable for large grinding machines and other handheld machines. The following are the normal specifications of turbo segment diamond cup grinding wheels:

Diameter	Segment Height	Connection	Grit
5"/125mm		M14 M16	6#
6"/150mm	/ <b>T</b> OIIIII	5/8"-11 20mm 22.23mm Snail Lock	16#
7"/180mm	ı/_IIImm		30# 60#
8"/200mm	7-10mm		120#
9"/230mm	7-10mm		

The above specifications just a reference for you.

Other specifications can be ordered by client.



#### **Single/double Row Diamond Cup Grinding Wheels:**

Single/double row diamond cup grinding wheels are designed for surface restoration or maint enance of granite,marble,concrete and other stone.

These single/double row diamond cup grinding wheels are suitable for large grinding machine s and other hand-held machines.

The following are the normal specifications of single/double row diamond cup grinding wheels  $\cdot$ 

Diameter	Segment Height	Connection	Grit
3"/75mm	5mm/6mm	M14 M16	35#
4"/100mm	5mm/6mm	M18 M20	50#
4.5"/115mm	5mm/6mm	5/8"-11 20mm 22.23mm	120#
5"/125mm	5mm/6mm	Snail Lock	400#
6"/150mm	5mm/6mm		
7"/180mm	5mm/6mm		
8"/200mm	5mm/6mm		
9"/230mm	5mm/6mm		

The above specifications just a reference for you.

Other specifications can be ordered by client.





#### **Continuous Rim Diamond Cup Grinding Wheels:**

Continuous rim diamond cup grinding wheels are designed for surface restoration or mainten ance of granite,marble,concrete and other stone.

These Continuous rim diamond cup grinding wheels are suitable for large grinding machines and other hand-held machines.

The following are the normal specifications of Continuous rim diamond cup grinding wheels:

Diameter	Segment Height	Connection	Grit No.
4"/100mm		M14 M16	30#
4.5"/115mm	5mm/6mm	M18 M20	60 "
5"/125mm	5mm/6mm	5/8"-11 20mm 22.23mm	60#
6"/150mm	5mm/6mm	Snail Lock	120#
7"/180mm	5mm/6mm		120 "
8"/200mm	5mm/6mm		
9"/230mm	5mm/6mm		

The above specifications just a reference for you.

Other specifications can be ordered by client.



## **Electroplate/vacuum Brazed Diamond Cup Grinding Wheels:**

Electroplate/vacuum brazed diamond cup grinding wheels are designed for surface restoration or maintenance of granite, marble, concrete and other stone.

These electroplate/vacuum brazed diamond cup grinding wheels are suitable for large grinding machines and other hand-held machines.

The following are the normal specifications of electroplate/vacuum brazed diamond cup grind ing wheels:

Diameter	Segment Height	Connection	Grit
4"/100mm	2mm	20mm	30#
5"/125mm	2mm	20mm	60 "
6"/150mm	2mm	20mm	60#
7"/180mm	2mm	20mm	120#
8"/200mm	2mm	20mm	120 %

The above specifications just a reference for you.

Other specifications can be ordered by client.



# **Special segment diamond cup grinding wheels:**

Special segment diamond cup grinding wheels are designed for surface restoration or mainte nance of granite, marble, concrete and other stone.

These special segment diamond cup grinding wheels are suitable for large grinding machines and other hand-held machines.

The following are the normal specifications of special segment diamond cup grinding wheels:

Diameter	Segment	Connection	Grit
	Height		

4"/100mm	5mm/6mm		35#
4.5"/115mm	5mm/6mm		50#
5"/125mm	5mm/6mm	5/8"-11 20mm 22.23mm	120#
6"/150mm	5mm/6mm		400#
7"/180mm	5mm/6mm		
8"/200mm	5mm/6mm		
9"/230mm	5mm/6mm		

The above specifications just a reference for you.

Other specifications can be ordered by client.





# **Packing & Delivery:**

We will deliver within seven days of your payment, diamond cup grinding wheels are packed in cartons.

We can also pack the diamond cup grinding wheels according to your requirements.

Special diamond cup grinding wheels delivery through consultation.

# **Contact Us:**

# Fujian Nanan frameway Machinery Co.,Ltd.

No.605 Huahui Center, Shuitou Town 362342 Quanzhou, Fujian, China

**TEL:** (+86)595-86990206 / **S** Fax: (+86)595-86990220

- **Mobile/WhatsApp/Wechat:**(+ 86) 18650679939
- E-mail: boreway@boreway.com
- **Lyon Chang**