

Preparation:

Discs must be cut at a right angle to the surface of the disc, and the edges must be chamfered, and the surface must

be smooth.

Discs must be cut at a right angle to the surface of the disc on.It is recommended, chamfered, and the edges must be chamfered.

Assembly:

Discs must be cut at a right angle to the surface of the disc. 1.Ensure

the disc is cut at a right angle to the surface of the disc & amp; 2.Designed; the disc is cut at a right angle to the surface of the disc.

the disc is cut at a right angle to the surface of the disc. 3.Well

4.Wheel the disc is cut at a right angle to the surface of the disc. The disc is cut at a right angle to the surface of the disc. The disc is cut at a right angle to the surface of the disc. The disc is cut at a right angle to the surface of the disc.

Installation:

Follow the instructions for the installation of the disc. The disc is cut at a right angle to the surface of the disc.

Disc Size	Disc Thickness	Disc Material	Disc Grade
105mm (4 ")	5/8 "-11	5 Discs	Disc (# 30) Disc (# 60) Disc (# 120)
115mm (4.5 ")	20mm		
125mm (5 ")	22.23mm		
150mm (6 ")	M14		
180mm (7 ")	Disc Thickness		

Discs must be cut at a right angle to the surface of the disc. clients.Other discs must be cut at a right angle to the surface of the disc.

Discs must be cut at a right angle to the surface of the disc. The disc is cut at a right angle to the surface of the disc.

