Introduction:

Concrete 150mm diamond chamfering grinding wheel are used for profiling and polishing the edge, side of stone ,elevator door cover and frame of fireplace .Their merits are extremely high glos sy surface , and high accuracy in size and shape.

Features:

1.Different shapes and sizes are available.

2.Good balance and stable performance.

3.Sintered segment is aggressive for easy and quick stock removal.

Specifications:

The followings are the normal specification of our concrete diamond chamfering grinding wheel:

Product Name	Diameter	Thickness	Inner Hole	Application	Shape Type
Diamond grinding wheel	150mm	20/30/40	30	Bullnose SingleDupont SingleBullnose HalfBullnose HalfRadius SingleMarbleThreshold Single EdOther stoneOgee BullnoseBevel DoubleOgee DoubleRadius TopChamferOther Types	Dupont Single Bullnose Half Radius Single Threshold Single Edge
	200mm	20/30/40	30		
	250mm	20/30/40	50		
	300mm	20/30/40	50		Bevel Double Ogee Double
	350mm	20/30/40	50		Chamfer

The above specification just for a reference. Other specification can be ordered by customers.

Picture:





CE

Boreway Machinery Co., Ltd. www.diamondtools.top www.boreway.com

Similar product:

Vacuum brazed diamond profile sanding wheel for stone, vacuum brazed profiling wheel for granite





Boreway Machinery Co., Ltd. www.diamondtools.top www.boreway.com

Contact Us:

Fujian Nanan homeway Machinery Co.,Ltd.

🔀 No.605 Huahui Center, Shuitou Town 362342 Quanzhou, Fujian, China

TEL: (+86)595-86990206 / SFax: (+86)595-86990220

Mobile/WhatsApp/Wechat: (+ 86) 18650679939

E-mail: boreway@boreway.com

Lyon Chang