Introduction:

D75x20Tx20H Vacuum Brazed Grinding Wheel are used for profiling and polishing the edge, side of stone ,elevator door cover and frame of fireplace .Their merits are extremely high glossy surface , and high accuracy in size and shape.

Features:

- 1. Different shapes and sizes are available.
- 2.Good balance and stable performance.
- 3.Sintered segment is aggressive for easy and quick stock removal.

Specifications:

The followings are the normal specification of our D75x20Tx20H Vacuum Brazed Grinding Wheel:

g					
Product Name	Diameter	Thickness	Inner Hole	Application	Shape Type
	150mm	20/30/40	30		Bullnose Single
					Dupont Single
	200mm	20/30/40	30		Bullnose Half
				Granite	Radius Single
Diamond	250mm	20/30/40	50	Marble	Threshold Single Edge
grinding				Other stone	Ogee Bullnose
wheel		20/30/40	50		Bevel Double
	300mm				Ogee Double
	350mm	20/30/40	50		Radius Top
					Chamfer
					Other Types

The above specification just for a reference. Other specification can be ordered by customers.

Picture:

D75x20Tx20H Vacuum Brazed Grinding Wheel





Boreway Machinery Co., Ltd. www.diamondtools.top www.boreway.com





Boreway Machinery Co., Ltd. www.diamondtools.top www.boreway.com

Related Product:

Vacuum Brazed CNC Profiling Wheel For Marble D67*37T*35H





Boreway Machinery Co., Ltd. www.diamondtools.top www.boreway.com

Contact us:

Fujian Nanan Boreway Machinery CO.,Ltd.

ADD:Shuitou Town,Quanzhou,Fujian,China

Post Code:362342

TEL:(+86)595-86990206

FAX:(+86)595-86990220

Skype:boreway02

Whatsapp:(+86)18359335376

Facebook:Sherry Huang

Wechat:Sherry_154

Email:boreway02@boreway.net