

Introduction:

Diamond construction thin wall core drill bit are suitable for stand drilling machine, electrical hand-held drillers to drill concrete, masonry, brick etc.

The flowing of water keeps the drill bit cool and provide fast removal of drilling debris.

Features:

1. Applicable for most stand drilling machines, hand-held drillers.
2. Good balance and stable performance.

Specifications:

The followings are the normal specifications of our Diamond construction thin wall core drill bit:

Product Name	Diameter	Segment Size	Segment No.	Length	Applications

Wet Construction Diamond Core Drill Bit	7/8"(22mm)	12x3.0x10	3	Can be customized	Concrete Brick Masonry
	1"(25mm)	12x3.0x10	4		
	1.18"(29mm)	12x3.0x10	4		
	1.25"(32mm)	16x3.0x10	4		
	1.38"(35mm)	16x3.0x10	4		
	1.50"(38mm)	16x3.0x10	5		
	1.63"(42mm)	16x3.0x10	5		
	1.75"(45mm)	16x3.0x10	6		
	1.88"(48mm)	16x3.0x10	6		
	2"(52mm)	16x3.0x10	7		
	2.25"(57mm)	22x3.5x10	5		
	2.50"(63mm)	22x3.5x10	6		
	2.75"(70mm)	22x3.5x10	7		
	3"(76mm)	22x3.5x10	8		
	3.25"(82mm)	22x3.5x10	9		
	3.50"(89mm)	22x3.5x10	10		
	4"(102mm)	22x3.5x10	10		
	4.25"(108mm)	22x3.5x10	11		
	4.50"(114mm)	22x3.5x10	11		
	4.75"(120mm)	24x4.0x10	11		
	5"(127mm)	24x4.0x10	11		
	5.5"(140mm)	24x4.0x10	12		
	5.75"(146mm)	24x4.0x10	13		
	6"(152mm)	24x4.0x10	13		
	6.25"(159mm)	24x4.0x10	14		
	6.5"(165mm)	24x4.0x10	15		
	7"(178mm)	24x4.0x10	16		
	8"(203mm)	24x4.5x10	18		
	9"(229mm)	24x4.5x10	20		
	10"(254mm)	24x4.5x10	23		
	11"(280mm)	24x5.0x10	25		
	12"(305mm)	24x5.0x10	27		
	13"(330mm)	24x5.5x10	30		
	14"(356mm)	24x5.5x10	32		

The above specifications are for reference, other specifications can be ordered by customers.

Picture:

boreway®

ISO 9001
SGS

CE



Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

similar products:

[Electroplating diamond anchor bit for construction:](#)

boreway®



Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com