Introduction:

Metal Bond & Resin Filled Zero Tolerance Grinding Wheel 1" (25mm) to 4"(100mm) for grinding and polishing sink holes on the slab,

kitchens, countertops, etc., which is the most effective way to grind and polish the tight radius.

Metal Bond & Resin Filled Zero Tolerance Grinding Wheel are are designed for stock removal on granite marble by grinding a way excess

stone. Resin-filled wheel: Excellent for stock removal, resin-filled design greatly reduces bounce and minimizes chipping.

These sink wheels are the fastest way to remove material after cutting out sink holes. They are used for very aggressive grin ding

applications and removal of stock on variety materials including granite, concrete, limestone, marble, block, terazzo and more.

Features:

- 1. High efficiency, long lifespan and fast milling speed.
- 2.Perfect balance with zero vibration and stable performance.
- 3.Smoother milling without stone edge damage.
- 4. Greatly reduces bounce and minimizes chipping.

Specifications:

The followings are the normal specifications of our Metal Bond & Resin Filled Zero Tolerance Grinding Wheel:

Code No.	Diameter	Grit No.	Working Method	Segment Length	Bore
BW-ZTW-M02-01	25mm(1")	Rough Medium Hard	Wet or Dry	20mm 35mm 45mm	M14 5/8"-11 1/2"G
BW-ZTW-M02-02	50mm(2")				
BW-ZTW-M02-03	75mm(3")				
BW-ZTW-M02-04	100mm(4")				

The above specifications are for reference, other specifications can be ordered by customers.

Quality:Premium.

Related Pictures:

The following is a zero tolerance wheel several common forms:

Segmented Zero Tolerance Grinding Wheel \square



Continuous Zero Tolerance Grinding Wheel \square



Resin Filled Zero Tolerance Grinding Wheel





Boreway Machinery Co., Ltd. www.boreway.com





Boreway Machinery Co., Ltd. www.boreway.com

Resin Bond Diamond Drum Wheels $\[\]$





Boreway Machinery Co., Ltd. www.boreway.com

