

Introduction:

Sintered tuck point blade for concrete offers extra fast and efficient removal of motor joints in brick, block or stone for exterior building surface,interior floors and walls; The design with sectional block segments and sinter tuck point has certain function of cuttingdischarge and heatdissipation□used for slotting the surace of stone and concrete.

Features:

- 1.High quality and good efficiency.
- 2.Long lifespan and stable performance.
- 3.Has certain function of cuttingdischarge and heatdissipation.

Specifications:

The followings are the normal specifications of our normal tuck point blade for concrete:

Product Name	Outer Diameter		Segment Width		Arbor	Segment Height	Segment Number
Sintered Tuck Point Blade for concrete	Inches	mm	Inches	mm			
	4"	105	0.250"	6.4	7/8"	8mm	8
	4.5"	115	0.250"	6.4	7/8"	8mm	8
	5"	127	0.250"	6.4	7/8"	8mm	10
	6"	153	0.250"	6.4	7/8"	8mm	12
	7"	178	0.250"	6.4	7/8"	8mm	14
	8"	203	0.250"	6.4	7/8"	8mm	16
	9"	229	0.250"	6.4	7/8"	8mm	18

The above specifications are for reference, other specifications can be ordered by customers.

Quality:Normal,Good quality,Premium.

boreway®



Boreway Machinery Co., Ltd.
www.boreway.com