



2T

2.

2.

2020年12月20日

□□□□	□□□
□□□□	2□□T□□□□□□□□
□□□□□□□□□□	16-270□etc□
□□□	□□□□□□□□□□
C□□□	3 X M6□□□M8□□□□□□□□
□□□	□□□□□□□□□□□□
□□□	□□□□□□□□□□
□□□□	□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□

[illegible][illegible]

2 T

T Shape Segments



3 X M6 or M8 or Bare Holes

Diamond Grinding Shoes



3 X M6/M8 Thread Holes



3 X Bare Holes

1.M63


2. 3mm M8 bolts

3. 3mm bolts

Concrete floor grinding


Concrete floor grinding

2. Concrete floor grinding process



Concrete Floor Grinding

METAL BOND DIAMOND GRINDING PLATES FOR HTC, LAVINA, HUSQVARNA CONNECTION:





CONCRETE HARDNESS	Xtreme Hard	Very Hard	Hard	Medium Hard	Soft	Very Soft
PSI	6500–9000	5000–7000	4000–5000	3000–4000	1500–3500	1000–2000
MPA	C50–C65	C40–C55	C30–C50	C20–C40	C15–C25	C10–C20
CODE	XHF	VHF	HF	MHF	SF	VSF
COLOUR						



□□□□□□□□

1. □□□□□□□□□□□□□□□□□□
2. □ □□□□□□□□□□□□□□□□□
3. □□□□□OEM□□□□□□□□□□□□□□□□□□□□□□□□□□□□
4. □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
5. □ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□

1. □□□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
 □□□□□□□8□□□□□□□□□□□□□□□□□□□□□□□□□□□□

