[illegible]

## [illegible]

[illegible]

[illegible]

## [illegible]

[illegible]

| | |
|---|---|
| [illegible] | Boreway |
| [illegible]<?xml:namespace prefix = o /> | |
| [illegible] | [illegible] |
| [illegible]RPM | 12,000 |
| [illegible] | 5/16 "* 24 |
| [illegible] | 3[illegible]4[illegible]5[illegible] |
| [illegible] | [illegible] |
| [illegible] | [illegible] |
| [illegible] | [illegible] |

[illegible]

## [illegible]

[illegible]

5 Inch
4 Inch
3 Inch
5" Sanding Pad
Size:
5/16" *24
threads
Density:
Medium
Soft
Professional
Dual Action
Random Orbital
Sanding Pad
Max Operation Speed :
12,000 R.P.M
4" Sanding Pad
Max Operation Speed :
12,000 R.P.M
3" Sanding Pad

Material: Foam
3" Sanding Pad

Thread: 5/16"*24
5" Sanding Pad
Size: 5/16" *24 threads
Density:
Medium
Soft
Professional Dual Action Random Orbital Sanding Pad
Max Operation Speed : 12,000 R.P.M

Strong adhesion,
not easy to fall off.

[illegible]

[illegible]

Electrodrill

Angle grinder

Polisher

□□□

1.□□□□□□

2.□□□□□□

3.□□□□□□□□□□□□□□□

4.□□□□□□□□□□□□□□

## □□□

1.□□□□□□□□□□□□□

2.□□□□□□□□□□□□□□□□□

3.□□□□□□□□□□□□□□□□□□□□□□□□□□□□

## □□□□□

**5/16 "-24□□□□□□□□□□□□□**

**5□□□□□□□□□□□□□□□□**

## □□□□□□□□□□

## [illegible]

1.[illegible]

2[illegible]

3.[illegible]OEM[illegible]

4.[illegible]

5[illegible]

## [illegible]

**1.**[illegible]

[illegible]

[illegible]

[illegible]

[illegible]8[illegible]

[illegible]

[illegible]
[illegible]
[illegible]
[illegible]
[illegible]

**3.**[illegible]
[illegible]
[illegible]
[illegible]
[illegible]

## [illegible]

1.[illegible]
2.[illegible]
3.[illegible]

## [illegible]


Fujian Nanan boreway Machinery Co.,Ltd.

[illegible]362342[illegible]Hu[illegible]605[illegible]

**TEL**[illegible] [illegible]+86[illegible]595-86990206 / [illegible] [illegible]+86[illegible]595-86990220

[illegible]**/ WhatsApp / Wechat**[illegible] [illegible]+ 86[illegible] 13557694058

**E**[illegible] boreway07@boreway.net

[illegible]