Introduction:

- 1. HTC diamond floor grinding blocks are designed for used in HTC floor grinding machines to remove the expoxy,glue,paint and other uneven coating of concrete,terrazzo and stone floor, show a smooth and brand new floor. It is convenient for subsequent grinding and polishing treatment;
- 2. The diamond grinding blocks use the standard HTC interface, It has 2 cuboid diamond segments. There have a variety of grits for your choice;
- 3. BOREWAY provide three kinds diamond segment bonds for different floors, soft, medium and hard. The grinding blocks we provide are belong to high quality, please do not confuse these blocks with other cheap blocks;
- 5. This grinding block is usually used on floor grinding machines with HTC interface, can be quickly installed and dismantled, greatly improving the efficiency of work.

Features:

- 1. We can provide soft, medium, hard bond designed specifically for various floors;
- 2. HTC connection, easy and guick replacement;
- 3. Different size segments can be custom.

Specification:						
Model No	Segment type	Segment materials	Srgment number	Grit No.	Bond	Connection
BW-HTC-MWT05	Cuboid	Diamond	2	6#, 16#, 25# 30#, 40#, 50#, 60# 80#, 100#, 120# 150#, 170#, 200#	Soft Midium Hard	HTC EZ change

Other connection and specification can be customized according to need.

Images:

Click here to visit our HTC DIAMOND GRINDING PADS.

boneway[®]



boreway[®]











If you want know more images, please contact us.

Click here to visit our HTC DIAMOND GRINDING PADS.

Related products:

2 arrow diamond bar concrete block pads with EZ change connection for HTC grinding machines





Contact us:

Fujian Nanan Boreway Machinery Co.,Ltd.

Address: Huahui Center 605, Shuitou Town, Quanzhou, Fujian, China

Post Code: 362342

TEL: (+86)595-86990206/(+86)18250633812

FAX: (+86)595-86990220

WhatsApp: +86-18359335376

Facebook: ChoisDong

Email: boreway.net