## **Production Description:**

Introduction[]

**Diamond calibrating diamond roller** is most commonly used to calibrate and achieve a uniform thickness on ceramic tiles surface before polishing. Thanks to the continuous technical improvement and the feedback from our customers, our **diamond calibrating diamond roller** are approved for their good sharpness, long working lifetime, low energy consumption, low working noise, excellent working effect and stable performance. Wet use only with sufficient water, Fast & Easy grinding, long life, perfect performance. All of our our products have been strictly tested before access to market.

Other specifications can be customized according to requirements.

# **Detailed Images:**

#### The following is the normal specification of diamond calibrating diamond roller:

Product Name	Out Diameter (mm)	Length (mm)	Spiral Number	Segment Size (mm)	Grit (#)
Diamond Calibrating Rollers	Ф180 - Ф320	320	5 6 7 12 16	9*12 9*15 6*10	
		400			30
		595			40
		645 (585)			50 60
		800 (740)			70
		800 (680)			80 100
		995 (935)			120
		1195 (1135)			140
		1600 (1540)			

The following shows only part of the product , other products can be customized according to your needs .

If you do not see the product you want, please contact us for more product images.





Above is a picture of our conventional diamond calibration rollers, Other specifications can be customized according to requirements.

## **Packing** □

We will deliver within seven days of your payment, diamond calibrating rollers are packed in wooden.

We can also pack the rollers according to your requirements.

Special specifications through consultation delivery.

### **Contact Us:**

Fujian Nanan Boreway Machinery Co.,Ltd.

Address: Hongxing Street, Shuitou Town, Quanzhou, Fujian, China,

**Post Code:** 362342

**TEL:** (+86)595-86990206/(+86)18250633812

**FAX:** (+86)595-86990220

**WhatsApp:**+86-18359335376

Facebook:Sherry Huang