Circular Cutting Blade Dry Wet Segmented Disc Tools Diamond Saw Disk For Title Porcelain Concrete



The following are normal specifications Cutting Blade Dry Wet Segmented Disk:

	iameter	Bore	Segment	Number of Segments	Seament	1					
	lameter	Bore	segment	Number of Segments	Segment						
Inci	h mm	Size(mm/inch)	Thickness(mm)	PCS	Height(mm)	4	105		35	6/8	8/10/12
4.3	110	32.3	6/8/9	8/10/12							
4.5	115	38.5	8	8/10/12							
5	125	37.5	9	8/10/12				16/20 22.23			
6	150	33.5	12	8/10/12				25.4 50			
7	180	35	14	8/10/12							
8	200	39.2	14	8/10/12							
9	230	34.4	18	8/10/12							

The above specifications is only for reference, other specifications may be available as per customer's demand.

Feature:

- 1. Great adaptability & No chipping
- 2. Different bonds are for different applications & precise segment size
- 3. Working safe, quiet, and precise, reducing cutting & working time

4. Cutting Blade Dry Wet Segmented Disk fast cutting & long life & Stable performance, High grade of diamonds

Support Sample Processing Customization

Style and Specifications



Contact Salesman

Due to the large number of product specifications and styles, in order to avoid conflicts, please contact the salesman before placing the order.

Provide Samples

The manufacturer supports the sample processing and customization, and the buyer provides the sample first to communicate the production requirements.





Mail Samples

According to the buyer's demand for proofing,the manufacturer needs the buyer to pay the proofing fee first, and the sample fee will be returned after the order is concluded.

Generate Order

The buyer receives the sample. If satisfied, place an order for batch production. After confirming the receipt,contact the salesman to return the proofing cost.



Attention when use:

1. Before saw blade installed, pollutions adhering between saw blade and flange shall be removed,

when installing saw blade, the marked direction shall be kept consistent with the rotating direction of electric tools, and flange shall be fastened by spanner attached to electric tools

2. Do not use any saw blade that has been deformed for being pressed of crashed

3. When operating, operator must wear safety helmet, safety footwear and goggles, protective glove, additionally, if necessary operator must use earplug, mask and so on

Cutting Blade Dry Wet Segmented Disk

1. The substrate is made of 65 manganese alloy steel, the thickness strictly abides by the product implementation standards, high strength, strong and stable;

2. The cutter head is made of high-quality diamond and metal powder mixed and sintered for sharp and ultra-long cutting;

3. The optimized and reasonable cooperation of the base body and the cutter head makes the saw blade not burn teeth, lack of saws, and does not shake, and the feel is easy and fast;

4. The manufacturers ship directly, various specifications are flexibly customized, and the quality is reliable and the price is affordable.

5. Because the size of the saw blade is small and medium, it is easy to use, stable cutting without deformation, and flexible usage. It is one of the commonly used diamond cutting series.

Our factory use original high grade diamond


Other factory mix second diamond selected from waste segment



Our blade cutting effect



Other supplier blade cutting effect



Applications:

Cutting Blade Dry Wet Segmented Disk Suitable for cutting ceramic tile, vitrified brick, microcrystalline stone, etc



Hot Sintered, Dry or Wet Use!



Applications machine:

Cutting Blade Dry Wet Segmented

Disk use for angle grinder, circular saw, masonry saw, table saw

Cutting effect:





Related Products:





About us:





Packing [] Delivery:

PS:

- 1. Tools packing in carton cases
- 2.By Air/Sea for batch goods, Airport/Port receiving
- 3.Less than 45kg, generally delivery by express(Door to Door]
- 4. When tools are in large quantities, they are packing in wooden cases



Our service:

- 1. Low order quantity: It can meet the test order you need.
- 2. Fast delivery: We get great discounts from freight forwarders.
- 3. OEM Acceptable: We can produce according to your samples or drawings.
- 4. Good quality: We have a strict quality control system. Has a good reputation in the market.

5. Good service: We regard our customers as God with a high degree of professionalism and enthusiasm.

FAQ:

1. If we want to order your product, how do we know your quality?

You can test with a small order, and then you will know the quality. Nowadays, many people in the world use Chinese products because of their high quality and high cost performance. We are a professional diamond tool manufacturer with more than 8 years of manufacturing experience.

2. Can you provide samples for free?

We do not provide free samples. Based on years of experience, we believe that customers will want them because of their reliable quality. By purchasing samples, we will cherish and appreciate them and make them get more. We are ready to offer our potential customers a special discount on samples. It's very important that you give us feedback, and we will

appreciate it.

3. Does your company accept customization?

Of course, we accept customization. Including different colors, cutting objects, etc. We can also tag your own label and company brand. If you want us to make any new products for you, just send your products to us. Whether it's drawings or samples, we have the ability to produce the same products. We will not sell these products to others, only customers can get permission.

Please note:

Please use high frequency Silver Welded machine instead of Fire to make the brazing, the welding time is only a few seconds, otherwise the diamond inside the segments will probably be damaged by the high temperature, then the cutting performance will be Reduced!

Contact us:

Fujian Nanan Manan Machinery Co.,Ltd.

🔀 No.605 Huahui Center, Shuitou Town 362342 Quanzhou, Fujian, China

TEL: (+86)595-86990206 / **Sax:** (+86)595-86990220

Mobile/WhatsApp/Wechat: (+ 86) 18650679939

E-mail: boreway@boreway.com

Lyon Chang