

Introduction:

- 1.D100x20Tx50H Diamond Segmented Standard Stubbing Wheel are used for surface milling and material removal for various granite and marble stone
2. It is been applied to router machines or CNC machines.
- 3.It is used to level off your slab before running your profile wheels.

Feature:

- 1.The unique design with good sharpness allows easy dust removal, low noise and safety.
- 2.With feature of high efficiency,accuracy in shape and size.
- 3.Good performance and long lifespan.

Specification:

Mill milling wheel of the conventional specifications:

| Diameter / mm | Segment height / mm | Inner Hole / mm | Connection | Grit NO. | Machine |
|-----------------------|---------------------|-----------------|---|-----------------------------------|------------------------------------|
| 50 86 100 90 | 20 30 40 | 10 50 | Φ 10-2 + 2Hole Φ 50-3 + 3Hole Φ 50-3 + 3Hole | 30/40 # 60 # 100 # 200 # | CNC machine and radial arm machine |

In order to improve the grinding efficiency of grinding wheel, we have some suggestions for the machine speed:

| RPM | Feed rate | Recommended depth |
|------|-----------------|-------------------|
| 4500 | 400-600mm / min | 3mm |

Other specifications can be customized after communication

Images:

[Click this link to browse other sizes of diamond standard stubbing wheel:](#)

boreway®



Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

boreway®



Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

Contact us:

Fujian Nanan Boreway Machinery Co.,Ltd.

Address: Huahui Center 605, Shuitou Town,Quanzhou, Fujian, China

Post Code: 362342

TEL: (+86)595-86990206/(+86)18250633812

FAX: (+86)595-86990220

WhatsApp/Wechat: +86-18359335376

Facebook: borewaysherry

Email: boreway02@boreway.net