

Introduction:

- 1.D20x60Tx1/2"G CNC Sinter Finger Bits For Processing Stone Slab are usually use after diamond core drill bits, fast removing dust,diamond sink wheel.
- 2.They are ideal for fast stock removal as well as truing up saw lines, which is designed to cut granite, engineered stone and marble,counter tops, kitchen tops and basins.
- 3.Usually mounted on CNC or Radial Arm machines, for hole grinding, anchor and blind hole.
- 4.Center water feed holes in each bit.
- 5.Please vertical using and add water when grinding,mostly for side grinding.

Features:

- 1.Faster Speed and Lasting longer
2. Less Noise and Low Ampere

Specification:

The normal size of D20x60Tx1/2"G CNC Sinter Finger Bits For Processing Stone Slab :

Diameter	Bore (mm)	Segment Length	Segment No.
20mm (3/4")	1/2 Gas (Male Thread) M14 5/8"-11	40mm 45mm 50mm 60mm	4-6pcs
25mm (1")			
30mm (1-1/4")			
35mm (1-3/8")			
40mm (1-5/8")			
50mm (2")			
60mm (2-3/8")			

The above specifications are for reference, other specifications can be ordered by customers.

[Click Here To Browse More Sizes And Shapes Of Diamond Finger Bit](#)

Images:

D20x60Tx1/2"G CNC Sinter Finger Bits For Processing Stone Slab

boreway®



Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

Contact us:

Fujian Nanan Boreway Machinery CO.,Ltd.

ADD:Shuitou Town,Quanzhou,Fujian,China

Post Code:362342

TEL:(+86)595-86990206

FAX:(+86)595-86990220

Skype:boreway02

Whatsapp:(+86)18359335376

Facebook:BorewaySherry

Wechat:Sherry_154

Email:boreway02@boreway.net