Description:

Dry use diamond core drill bits with vacuum brazed protection teeth D32*5/8"-11 are

produced by silver or laser welding.

It can be suitable for stand drilling machines or electrical hand-held drillers or CNC machine.

For drilling kinds of granite or hand stone.

Silver welded is better for wet use and laser welded is better for dry use.

Features:

- 1.Designed for drilling holes
- 2.Good stable and long lifespan.
- 3.Can be dry or wet use.

Specifications:

The following is the normal size of Dry use diamond core drill bits with vacuum brazed protection teeth:

22mm (7/8") 17/12x3x10 or (100mm) or M14	Code No.	Diameter	Segment Size	Use	Pipe Length	Welding Method	Adaptor
25mm (1") 17/12x3x10 Dry Laser Welding 1/2 c 29mm (1-1/8") 17/12x3x10 32mm (1-1/4") 16x3x10 35mm (1-3/8") 16x3x10 38mm (1-1/2") 16x3x10 42mm (1-5/8") 16x3x10 45mm (1-3/4") 16x3x10 50/51mm (2") 16x3x10 50/51mm (2") 16x3x10 60mm (2-3/4") 22x3.5x10 63mm (2-1/2") 22x3.5x10 63mm (3-1/2") 22x3.5x10 80mm (3-1/8") 22x3.5x10 80mm (3-1/8") 22x3.5x10 100mm (4") 22x3.5x10 110mm (4-3/8") 22x3.5x10	BW-DDB-S03	20mm (3/4")	17/12x3x10	Wet		or	5/8"-11 M14 1/2 Gas
29mm (1-1/8")17/12x3x1032mm (1-1/4")16x3x1035mm (1-3/8")16x3x1038mm (1-1/2")16x3x1042mm (1-5/8")16x3x1045mm (1-3/4")16x3x1050/51mm (2")16x3x1050/51mm (2")16x3x1060mm (2-3/8")22x3.5x1063mm (2-1/2")22x3.5x1070mm (2-3/4")22x3.5x1076mm (3")22x3.5x1080mm (3-1/8")22x3.5x10100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		22mm (7/8")	17/12x3x10	or			
32mm (1-1/4")16x3x1035mm (1-3/8")16x3x1038mm (1-1/2")16x3x1042mm (1-5/8")16x3x1045mm (1-3/4")16x3x1050/51mm (2")16x3x1057mm (2-1/4")22x3.5x1060mm (2-3/8")22x3.5x1063mm (2-1/2")22x3.5x1070mm (2-3/4")22x3.5x1080mm (3-1/8")22x3.5x1089mm (3-1/2")22x3.5x10100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		25mm (1")	17/12x3x10	Dry			
35mm (1-3/8")16x3x1038mm (1-1/2")16x3x1042mm (1-5/8")16x3x1045mm (1-3/4")16x3x1050/51mm (2")16x3x1057mm (2-1/4")22x3.5x1060mm (2-3/8")22x3.5x1063mm (2-1/2")22x3.5x1070mm (2-3/4")22x3.5x1076mm (3")22x3.5x1080mm (3-1/8")22x3.5x10100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		29mm (1-1/8")	17/12x3x10				
38mm (1-1/2")16x3x1042mm (1-5/8")16x3x1045mm (1-3/4")16x3x1050/51mm (2")16x3x1057mm (2-1/4")22x3.5x1060mm (2-3/8")22x3.5x1063mm (2-1/2")22x3.5x1070mm (2-3/4")22x3.5x1076mm (3")22x3.5x1080mm (3-1/8")22x3.5x10100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		32mm (1-1/4")	16x3x10				
42mm (1-5/8")16x3x1045mm (1-3/4")16x3x1050/51mm (2")16x3x1057mm (2-1/4")22x3.5x1060mm (2-3/8")22x3.5x1063mm (2-1/2")22x3.5x1070mm (2-3/4")22x3.5x1076mm (3")22x3.5x1080mm (3-1/8"22x3.5x1089mm (3-1/2")22x3.5x10100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		35mm (1-3/8")	16x3x10				
45mm (1-3/4")16x3x1050/51mm (2")16x3x1057mm (2-1/4")22x3.5x1060mm (2-3/8")22x3.5x1063mm (2-1/2")22x3.5x1070mm (2-3/4")22x3.5x1076mm (3")22x3.5x1080mm (3-1/8"22x3.5x1089mm (3-1/2")22x3.5x10100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		38mm (1-1/2")	16x3x10				
50/51mm (2")16x3x1057mm (2-1/4")22x3.5x1060mm (2-3/8")22x3.5x1063mm (2-1/2")22x3.5x1070mm (2-3/4")22x3.5x1076mm (3")22x3.5x1080mm (3-1/8")22x3.5x1089mm (3-1/2")22x3.5x10100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		42mm (1-5/8")	16x3x10				
57mm (2-1/4")22x3.5x1060mm (2-3/8")22x3.5x1063mm (2-1/2")22x3.5x1070mm (2-3/4")22x3.5x1076mm (3")22x3.5x1080mm (3-1/8"22x3.5x1089mm (3-1/2")22x3.5x10100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		45mm (1-3/4")	16x3x10				
60mm (2-3/8")22x3.5x1063mm (2-1/2")22x3.5x1070mm (2-3/4")22x3.5x1076mm (3")22x3.5x1080mm (3-1/8")22x3.5x1089mm (3-1/2")22x3.5x10100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		50/51mm (2")	16x3x10				
63mm (2-1/2")22x3.5x1070mm (2-3/4")22x3.5x1076mm (3")22x3.5x1080mm (3-1/8")22x3.5x1089mm (3-1/2")22x3.5x10100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		57mm (2-1/4")	22x3.5x10				
70mm (2-3/4")22x3.5x1076mm (3")22x3.5x1080mm (3-1/8")22x3.5x1089mm (3-1/2")22x3.5x10100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		60mm (2-3/8")	22x3.5x10				
76mm (3")22x3.5x1080mm (3-1/8"22x3.5x1089mm (3-1/2")22x3.5x10100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		63mm (2-1/2")	22x3.5x10				
80mm (3-1/8"22x3.5x1089mm (3-1/2")22x3.5x10100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		70mm (2-3/4")	22x3.5x10				
89mm (3-1/2")22x3.5x10100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		76mm (3")	22x3.5x10				
100mm (4")22x3.5x10110mm (4-3/8")22x3.5x10		80mm (3-1/8"	22x3.5x10				
110mm (4-3/8") 22x3.5x10		89mm (3-1/2")	22x3.5x10				
		100mm (4")	22x3.5x10				
127mm (5") 24x4x10		110mm (4-3/8")	22x3.5x10				
		127mm (5")	24x4x10				

The above specification just a reference for customer. Other specification can be ordered by clients.

Picture:

Dry use diamond core drill bits with vacuum brazed protection teeth



Related product: Dimaond core drill bits with double threads D70*110L*1/2"G/M14