Introduction:

Granite chamfering profiling

wheel are used for profiling and polishing the edge, side of stone , elevator door cover and frame of fireplace . Their merits are extremely high glossy surface , and high accura cy in

size and shape.

Features:

- 1. Different shapes and sizes are available.
- 2.Good balance and stable performance.
- 3. Sintered segment is aggressive for easy and quick stock removal.

Specifications:

The followings are the normal specification of our granite chamfering profiling wheel:

Product Name	Diameter	Thickness	Inner Hole	Application	Shape Type
Diamond grinding wheel	150mm	20/30/40	30	Bullnose Single Dupont Single Bullnose Half Radius Single Threshold Single Ed Other stone Ogee Bullnose Bevel Double Ogee Double Radius Top Chamfer Other Types	Dupont Single Bullnose Half
	200mm	20/30/40	30		
	250mm	20/30/40	50		Threshold Single Edge
	300mm	20/30/40	50		Bevel Double Ogee Double
	350mm	20/30/40	50		

The above specification just for a reference. Other specification can be ordered by customers.

Picture:





Boreway Machinery Co., Ltd. www.diamondtools.top www.boreway.com

Similar product:





Boreway Machinery Co., Ltd. www.diamondtools.top www.boreway.com

Contact Us:

Fujian Nanan homeway Machinery Co.,Ltd.

No.605 Huahui Center, Shuitou Town 362342 Quanzhou, Fujian, China

TEL: (+86)595-86990206 / **Sepanding** Fax: (+86)595-86990220

Mobile/WhatsApp/Wechat: (+ 86) 18650679939

E-mail: boreway@boreway.com

Lyon Chang