

Introduction:

Diamond Bush Hammer Concrete Surface D150x3Tx45sx40H is used on manual grinding machines or auto/semi-auto bush hammered machines to process bush hammered litchi surface on concrete granite, marble and other stone surface.

The processing surface can be very uniform and seems real and natural.

The rollers can be changed conveniently, greatly reduced the production costs.

Features:

1. For granite has high grinding efficiency and long lifespan.
2. Uniform, real and natural processing surface.
3. Much lower production costs compared with traditional processing method.

Specifications:

The followings are the normal specifications of our **Diamond Bush Hammer Concrete Surface** :

Product Name	Outer Diameter		Roller Quantity	Segment Quantity	Connection
	Inch	mm			
Bush Hammer Plate	5	125	3	30	M14 M16 5/8''-11 42mm 47mm 50mm
	6	150	4	45	
			3	30	
	8	200	6	45	
			4	30	
	10	250	8	45	
			5	30	
	12	300	10	45	
			6	30	

The above specification just a reference for clients. Other specifications can be ordered by customers.

Picture:

Diamond Bush Hammer Concrete Surface D150x3Tx45sx40H



Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

Related Product:

Hand Held Concrete Polisher D150x3Tx45sx40H



Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

Contact us:

Fujian Nanan Boreway Machinery CO.,Ltd.

ADD:Shuitou Town,Quanzhou,Fujian,China

Post Code:362342

TEL:(+86)595-86990206

FAX:(+86)595-86990220

Email:boreway@boreway.com