

Description:

Diamond Hole Saw Drill Bit With Double Theads For Granite D35*110L*1/2"G/M14 are produced by silver or laser welding.

It can be suitable for stand drilling machines or electrical hand-held drillers or CNC machine.

For drilling kinds of granite or hand stone.

Silver welded is better for wet use and laser welded is better for dry use.

Features:

- 1.Designed for drilling holes
- 2.Good stable and long lifespan.
- 3.Can be dry or wet use.

Specifications:

The following is the normal size of **Diamond Hole Saw Drill Bit With Double Theads:**

Code No.	Diameter	Segment Size	Use	Pipe Length	Welding Method	Adaptor
BW-DDB-S03	20mm (3/4")	17/12x3x10	Wet	4"	Silver Welding	5/8"-11
	22mm (7/8")	17/12x3x10	or	(100mm)	or	M14
	25mm (1")	17/12x3x10	Dry		Laser Welding	1/2 Gas
	29mm (1-1/8")	17/12x3x10				
	32mm (1-1/4")	16x3x10				
	35mm (1-3/8")	16x3x10				
	38mm (1-1/2")	16x3x10				
	42mm (1-5/8")	16x3x10				
	45mm (1-3/4")	16x3x10				
	50/51mm (2")	16x3x10				
	57mm (2-1/4")	22x3.5x10				
	60mm (2-3/8")	22x3.5x10				
	63mm (2-1/2")	22x3.5x10				
	70mm (2-3/4")	22x3.5x10				
	76mm (3")	22x3.5x10				
	80mm (3-1/8")	22x3.5x10				
	89mm (3-1/2")	22x3.5x10				
	100mm (4")	22x3.5x10				
	110mm (4-3/8")	22x3.5x10				
	127mm (5")	24x4x10				

The above specification just a reference for customer.Other specification can be ordered by clients.

Picture:

Diamond Hole Saw Drill Bit With Double Theads For Granite D35*110L*1/2"G/M14