

**Introduction:**

Turbo segments for construction diamond core drill bits are suitable for drilling cured reinforced concrete, green concrete or stone material. Under same bond conditions, the drilling speed of this turbo segments is much faster than normal flat segments.

**Features:**

1. Turbo segment provide higher drilling efficiency.
2. Wet or dry drilling.
3. Long lifespan and stable performance.

**Specifications:**

The followings are the normal specifications of our turbo segment for construction diamond core drill bit:

Product Name	Diameter	Segment Width	Segment No.	Applications

Turbo Segment For Construction Diamond Core Drill Bit	1.25"(32mm)	16x3.0x10	4	Concrete Brick Masonry
	1.38"(35mm)	16x3.0x10	4	
	1.50"(38mm)	16x3.0x10	5	
	1.63"(42mm)	16x3.0x10	5	
	1.75"(45mm)	16x3.0x10	6	
	1.88"(48mm)	16x3.0x10	6	
	2"(52mm)	16x3.0x10	7	
	2.25"(57mm)	24x3.5x10	5	
	2.50"(63mm)	24x3.5x10	6	
	2.75"(70mm)	24x3.5x10	7	
	3"(76mm)	24x3.5x10	8	
	3.25"(82mm)	24x3.5x10	9	
	3.50"(89mm)	24x3.5x10	10	
	4"(102mm)	24x3.5x10	10	
	4.25"(108mm)	24x3.5x10	11	
	4.50"(114mm)	24x3.5x10	11	
	4.75"(120mm)	24x4.0x10	11	
	5"(127mm)	24x4.0x10	11	
	5.5"(140mm)	24x4.0x10	12	
	5.75"(146mm)	24x4.0x10	13	
	6"(152mm)	24x4.0x10	13	
	6.25"(159mm)	24x4.0x10	14	
	6.5"(165mm)	24x4.0x10	15	
	7"(178mm)	24x4.0x10	16	
	8"(203mm)	24x4.5x10	18	
	9"(229mm)	24x4.5x10	20	
	10"(254mm)	24x4.5x10	23	
	11"(280mm)	24x5.0x10	25	
	12"(305mm)	24x5.0x10	27	
	13"(330mm)	24x5.5x10	30	
	14"(356mm)	24x5.5x10	32	

The above specifications are for reference, other specifications can be ordered by customers.

**Contact Us:**

**Fujian Nanan Boreway Machinery Co.,Ltd.**

**Address: Huahui Center 605, Shuitou Town,Quanzhou, Fujian, China.**

**Post Code: 362342**

**Tel.: 0086-595-86990206**

**Fax: 0086-595-86990220**

**Contact: Ally Huang**

**Mobile/WhatsApp: 0086-13559599186**

**Wechat: boreway05**

**Skype: boreway05**

**Facebook: 13559599186**

**E-mail: boreway05@boreway.net**

**Website: <http://www.diamondtools.top>**