Introduction:

Zero Tolerance Grinding Wheels (metal bond) 1" (25mm) to 4"(100mm) for grinding and polishing sink holes on the slab,

kitchens, countertops, etc., which is the most effective way to grind and polish the tight radius.

Zero Tolerance Grinding Wheels are designed for stock removal on granite marble by grinding away excess stone. These sink

wheels are the fastest way to remove material after cutting out sink holes. They are used for very aggressive grinding applications

and removal of stock on variety materials including granite, concrete, limestone, marble, block, terazzo and more.

Features:

- 1. High efficiency, long lifespan and fast milling speed.
- 2. Perfect balance with zero vibration and stable performance.
- 3. Smoother milling without stone edge damage.

Specifications:

The followings are the normal specifications of our zero tolerance grinding wheel supplier:

Code No.	Diameter	Grit No.	Working Method	Segment Length	Connection
BW-ZTW-M00-01	25mm(1")	Rough Medium Hard	Wet or Dry	20mm 35mm 45mm	M14 5/8"-11 1/2"G
BW-ZTW-M00-02	50mm(2")				
BW-ZTW-M00-03	75mm(3")				
BW-ZTW-M00-04	100mm(4")				

The above specifications are for reference, other specifications can be ordered by customers.

Quality:Premium.

Related Pictures

The following is a zero tolerance wheel several common forms:

Segmented Zero Tolerance Grinding Wheel



Continuous Zero Tolerance Grinding Wheel



Resin Filled Zero Tolerance Grinding Wheel





Boreway Machinery Co., Ltd. www.boreway.com





Boreway Machinery Co., Ltd. www.boreway.com

Resin Bond Diamond Drum Wheels $\[\]$





Boreway Machinery Co., Ltd. www.boreway.com

