Production Description:

Вступление:

Boreway diamond cup grinding wheels are usually used with large grinding machine and other hand-held grinding machines, these diamond cup grinding wheels are designed for the restoration or maintenance of granite, marble, and many other stone surface, Boreway diamond cup grinding wheels are polishing with quick speed and without scratch.

Our professional **diamond cup grinding wheels** are designed to ensure fast grinding and finishing of concrete, granite, and other stones in dry or wet conditions. Our diamond grinding wheels are available in three grits: coarse (30/40 grits) for fast stock removal, medium (70/80 grits) for moderate grinding, and fine (100-120 grits). We offer both diamond cup wheels with 5/8-11 thread, and velcro backed diamond grinding wheels for grinding concrete counter tops.

Using sequence From the thick number to the number, Polishes finally.

Преимущество:Our products export to Brazil, India, Australia, USA, Ukraine, Italy, Poland, Russia, more than 20 different countries. In these overseas markets,our cup grinding wheels enjoy a good reputation, we get good feedbacks about their corresponding test result, and also a long lifespan. so, we are confident in our products quality.

All of our our products have been strictly tested before access to market.

Other specification can be ordered by client.

Detailed Images:

Turbo Segment Diamond Cup Grinding Wheels:

Turbo segment diamond cup grinding wheels are designed for surface restoration or maintenance of granite, marble, concrete and other stone.

These diamond cup grinding wheels are suitable for large grinding machines and other hand-held machines.

The following are the normal specifications of turbo segment diamond cup grinding wheels:

Диаметр	Segment Высота	Связь	Grit
5"/125mm	7-10mm	M14 M16	6#
6"/150mm	7-10mm	5/8"-11	16#
7"/180mm	7-10mm	22.23mm	30# 60# 120#
8"/200mm	7-10mm		
9"/230mm	7-10mm		

The above specifications just a reference for you.



Single/double Row Diamond Cup Grinding Wheels:

Single/double row diamond cup grinding wheels are designed for surface restoration or maintenance of granite,marble,concrete and other stone.

These single/double row diamond cup grinding wheels are suitable for large grinding machines and other hand-held machines.

The following are the normal specifications of single/double row diamond cup grinding wheels:

Диаметр	Segment Высота	Связь	Grit
3"/75mm	, , ,	M14 M16	35#
4"/100mm	5mm/6mm	M18 M20	50#
4.5"/115mm	5mm/6mm	5/8"-11 20mm	120# 200#
5"/125mm	5mm/6mm	22.23mm	400#
6"/150mm	5mm/6mm	Snail Lock	
7"/180mm	5mm/6mm		
8"/200mm	5mm/6mm		
9"/230mm	5mm/6mm		

The above specifications just a reference for you.



Continuous Rim Diamond Cup Grinding Wheels:

Continuous rim diamond cup grinding wheels are designed for surface restoration or maintenance of granite, marble, concrete and other stone.

These Continuous rim diamond cup grinding wheels are suitable for large grinding machines and other hand-held machines.

The following are the normal specifications of Continuous rim diamond cup grinding wheels:

	1		
Диаметр	Segment	Связь	Grit No.
	Высота		
4"/100mm	1 '	M14 M16	30#
4.5"/115mm	5mm/6mm	M18 M20	60 "
5"/125mm	5mm/6mm	5/8"-11 20mm	60#
6"/150mm	5mm/6mm	22.23mm	120#
7"/180mm	5mm/6mm	Snail Lock	
8"/200mm	5mm/6mm		
9"/230mm	5mm/6mm		

The above specifications just a reference for you.



Electroplate/vacuum Brazed Diamond Cup Grinding Wheels:

Electroplate/vacuum brazed diamond cup grinding wheels are designed for surface restoration or maintenance of granite,marble,concrete and other stone.

These electroplate/vacuum brazed diamond cup grinding wheels are suitable for large grinding machines and other hand-held machines.

The following are the normal specifications of electroplate/vacuum brazed diamond cup grinding wheels:

Диаметр	Segment Высота	Связь	Grit
4"/100mm	2mm	20mm	30#
5"/125mm	2mm	20mm	60 "
6"/150mm	2mm	20mm	60#
7"/180mm	2mm	20mm	120#
8"/200mm	2mm	20mm	120 //

The above specifications just a reference for you.



Special segment diamond cup grinding wheels:

Special segment diamond cup grinding wheels are designed for surface restoration or maintenance of granite,marble,concrete and other stone.

These special segment diamond cup grinding wheels are suitable for large grinding machines and other hand-held machines.

The following are the normal specifications of special segment diamond cup grinding wheels:

Диаметр	Segment Высота	Связь	Grit
4"/100mm	, -	M14 M16	35#
4.5"/115mm		M18 M20	50#
5"/125mm	5mm/6mm	5/8"-11 20mm	120# 200#
6"/150mm	5mm/6mm	22.23mm	400#
7"/180mm	5mm/6mm	Snail Lock	
8"/200mm	5mm/6mm		
9"/230mm	5mm/6mm		

The above specifications just a reference for you.



Boreway Machinery Co., Ltd. www.diamondtools.top www.boreway.com



Boreway Machinery Co., Ltd. www.diamondtools.top www.boreway.com











Boreway Machinery Co., Ltd. www.diamondtools.top www.boreway.com



















Boreway Machinery Co., Ltd. www.diamondtools.top www.boreway.com



Boreway Machinery Co., Ltd. www.diamondtools.top www.boreway.com



Packing & Delivery:

We will deliver within seven days of your payment, diamond cup grinding wheels are packed in cartons.

We can also pack the diamond cup grinding wheels according to your requirements.

Special diamond cup grinding wheels delivery through consultation.

Связаться с нами:

Fujian Nanan functional Machinery Co.,Ltd.

- No.605 Huahui Center, Shuitou Town 362342 Quanzhou, Fujian, China
- **TEL:** (+86)595-86990206 / **Sepanding** Fax: (+86)595-86990220
- Mobile/ WhatsApp /Wechat:(+ 86) 18650679939
- **⊠**Эл. адрес: boreway@boreway.com
- **Lyon Chang**